

HIGH PRESSURE TEST PLUGS



The M Series High Pressure Test Plugs are designed for pressure testing at high pressure up to 3,000 p.s.i. After inserting the plug inside the pipe and when the nut on the stem is tightened the steel grips on the outer diameter of the plug grip against the inside diameter of the pipe and a neoprene seal cup is compressed to seal off the pipe. Hardened plated construction of all metal parts used in conjunction with the high quality neoprene "O" rings and seals assures a reliable and contamination free operation. All M Series test plugs are factory tested up to 3,000 p.s.i. depending on the size. Special sizes as large as 60" can be made to fit specific inside diameters.

CODE NO.	FITS INSIDE PIPE DIA. (IN INCHES)	UNEXPANDED OUTER DIAMETER (IN INCHES)	NOMINAL PIPE SIZE	SCHEDULE NUMBER	WALL THICKNESS (IN INCHES)	INSERTION LENGTH	WEIGHT (IN LBS.)
M40-1	1.049"	1.315"	1"	40	.133"	1 3/4"	1
M80-1	.957"	1.315"	1"	80	.179"	1 3/4"	1
M40-1 1/4	1.380"	1.660"	1 1/4"	40	.140"	2"	1 1/4
M80-1 1/4	1.278"	1.660"	1 1/4"	80	.191"	2"	1 1/4
M40-1 1/2	1.610"	1.900"	1 1/2"	40	.145"	2"	1 1/2
M80-1 1/2	1.500"	1.900"	1 1/2"	80	.200"	2"	1 1/2
M40-2	2.067"	2.375"	2"	40	.154"	2 1/4"	3
M80-2	1.939"	2.375"	2"	80	.218"	2 1/4"	3
M40-2 1/2	2.469"	2.875"	2 1/2"	40	.203"	2 1/2"	3 1/2
M80-2 1/2	2.323"	2.875"	2 1/2"	80	.276"	2 1/2"	3 1/2
M40-3	3.068"	3.500"	3"	40	.216"	3"	5
M80-3	2.900"	3.500"	3"	80	.300"	3"	5
M40-3 1/2	3.548"	4.000"	3 1/2"	40	.226"	3"	6 1/2
M80-3 1/2	3.364"	4.000"	3 1/2"	80	.318"	3"	6 1/2
M40-4	4.026"	4.500"	4"	40	.237"	3"	8
M80-4	3.826"	4.500"	4"	80	.337"	3"	8
M40-5	5.047"	5.563"	5"	40	.258"	3 1/4"	14
M80-5	4.813"	5.563"	5"	80	.375"	3 1/4"	14
M40-6	6.065"	6.625"	6"	40	.280"	3 1/2"	20
M80-6	5.761"	6.625"	6"	80	.432"	3 1/2"	20
M40-8	7.981"	8.625"	8"	40	.322"	3 3/4"	35
M80-8	7.625"	8.625"	8"	80	.500"	3 3/4"	35
M40-10	10.020"	10.750"	10"	40	.365"	4 1/2"	62
M80-10	9.750"	10.750"	10"	80	.500"	4 1/2"	62