

## MEDIUM PRESSURE TEST PLUGS



The Series MP Medium Pressure Test Plugs are capable of safely holding more pressure than the A, X or V series test plugs. These plugs have 4 to 12 (depending on the size) hardened set screws on the periphery having a knurled tip on which when tightened against the inside diameter of the pipe will offer additional friction to hold the plug under pressure. Maximum test pressures are dependent upon the friction of the test plug rubber with the inside of the pipe.

CODE NO.	FITS INSIDE PIPE DIA. (IN INCHES)	UNEXPANDED OUTER DIAMETER (IN INCHES)	STEM CONNECTION	WEIGHT (IN LBS.)
MP-04	4"	3 5/8"	1/2" NPT	6.00
MP-06	6"	5 1/2"	1/2" NPT	10.00
MP-08	8"	7 1/2"	1/2" NPT	16.00
MP-10	10"	9 1/2"	1/2" NPT	36.00
MP-12	12"	11 1/2"	1" NPT	52.00
MP-14	14"	13 5/8"	1" NPT	69.00
MP-15	15"	14 5/8"	1" NPT	75.00
MP-16	16"	15 5/8"	1" NPT	82.00
MP-18	18"	17 5/8"	1 1/4" NPT	102.00
MP-20	20"	19 5/8"	1 1/4" NPT	115.00
MP-21	21"	20 5/8"	1 1/4" NPT	125.00
MP-22	22"	21 5/8"	1 1/4" NPT	135.00
MP-24	24"	23 5/8"	1 1/4" NPT	156.00
MP-30	30"	29 5/8"	1 1/4" NPT	180.00
MP-36	36"	35 5/8"	1 1/4" NPT	220.00